SolidityScan | Powered by CRED SHIELDS

Security Assessment Report

BROT Token

24 Oct 2026

This security assessment report was prepared by SolidityScan.com, a cloud-based Smart Contract Scanner.

AICPA SOC | SCS Advocates OWASP OWASP Smart Contract Top 10 Security Risks & Vulnerabilities

Table of Contents

01 Vulnerability Classification and Severity

02 Executive Summary

03 Threat Summary

04 Findings Summary

05 Vulnerability Details

- CONTROLLED LOW-LEVEL CALL
- MERKLE LEAF CAN BE REUSED
- USE OF FLOATING PRAGMA
- MISSING EVENTS
- NONREENTRANT MODIFIER PLACEMENT
- OUTDATED COMPILER VERSION
- BLOCK VALUES AS A PROXY FOR TIME
- MISSING @AUTHOR IN NATSPEC COMMENTS FOR CONTRACT DECLARATION
- MISSING @DEV IN NATSPEC COMMENTS FOR CONTRACT DECLARATION
- MISSING @DEV IN NATSPEC COMMENTS FOR FUNCTIONS
- MISSING @INHERITDOC ON OVERRIDE FUNCTIONS
- MISSING NATSPEC COMMENTS IN SCOPE BLOCKS
- MISSING NATSPEC DESCRIPTIONS FOR PUBLIC VARIABLE DECLARATIONS
- MISSING @NOTICE IN NATSPEC COMMENTS FOR CONSTRUCTORS
- MISSING @NOTICE IN NATSPEC COMMENTS FOR FUNCTIONS
- NAME MAPPING PARAMETERS
- USE SCIENTIFIC NOTATION
- ABI ENCODE IS LESS EFFICIENT THAN ABI ENCODEPACKED
- ASSIGNING TO STRUCTS CAN BE MORE EFFICIENT
- AVOID RE-STORING VALUES

AVOID ZERO-TO-ONE STORAGE WRITES
CHEAPER CONDITIONAL OPERATORS
CHEAPER INEQUALITIES IN IF()
CHEAPER INEQUALITIES IN REQUIRE()
DEFINE CONSTRUCTOR AS PAYABLE
GAS INEFFICIENCY DUE TO MULTIPLE OPERANDS IN SINGLE IF/ELSEIF CONDITION
GAS OPTIMIZATION FOR STATE VARIABLES
PUBLIC CONSTANTS CAN BE PRIVATE
SIMILAR DATATYPES CAN BE PACKED TOGETHER
SPLITTING REQUIRE STATEMENTS
STORAGE VARIABLE CACHING IN MEMORY
SUPERFLUOUS EVENT FIELDS

05 Scan History

06 Disclaimer

01. Vulnerability Classification and Severity

Description

To enhance navigability, the document is organized in descending order of severity for easy reference. Issues are categorized as ***Fixed***, ***Pending Fix***, or ***Won't Fix***, indicating their current status. ***Won't Fix*** denotes that the team is aware of the issue but has chosen not to resolve it. Issues labeled as ***Pending Fix*** state that the bug is yet to be resolved. Additionally, each issue's severity is assessed based on the risk of exploitation or the potential for other unexpected or unsafe behavior.

Critical

The issue affects the contract in such a way that funds may be lost, allocated incorrectly, or otherwise result in a significant loss.

High

High-severity vulnerabilities pose a significant risk to both the Smart Contract and the organization. They can lead to user fund losses, may have conditional requirements, and are challenging to exploit.

Medium

The issue affects the ability of the contract to operate in a way that doesn't significantly hinder its behavior.

Low

The issue has minimal impact on the contract's ability to operate.

Informational

The issue does not affect the contract's operational capability but is considered good practice to address.

Gas

This category deals with optimizing code and refactoring to conserve gas.

02. Executive Summary



BROT Token

Uploaded Solidity File(s)

Language	Audit Methodology	Website
Solidity	**Static Scanning**	-
Publishers/Owner Name	**Organization**	**Contact Email**
-	-	-



Security Score is AVERAGE


The SolidityScan score is calculated based on lines of code and weights assigned to each issue depending on the severity and confidence. To improve your score, view the detailed result and leverage the remediation solutions provided.

This report has been prepared for BROT Token using SolidityScan to scan and discover vulnerabilities and safe coding practices in their smart contract including the libraries used by the contract that are not officially recognized. The SolidityScan tool runs a comprehensive static analysis on the Solidity code and finds vulnerabilities ranging from minor gas optimizations to major vulnerabilities leading to the loss of funds. The coverage scope pays attention to all the informational and critical vulnerabilities with over 700+ modules. The scanning and auditing process covers the following areas:

Various common and uncommon attack vectors will be investigated to ensure that the smart contracts are secure from malicious actors. The scanner modules find and flag issues related to Gas optimizations that help in reducing the overall Gas cost It scans and evaluates the codebase against industry best practices and standards to ensure compliance It makes sure that the officially recognized libraries used in the code are secure and up to date.

The SolidityScan Team recommends running regular audit scans to identify any vulnerabilities that are introduced after BROT Token introduces new features or refactors the code.

03. Threat Summary



Moderate Risk

66.5/100

Your smart contract has been assessed and assigned a **Moderate Risk** threat score. The score indicates the likelihood of risk associated with the contract code.

The contract can mint new tokens.

Minting functions are often utilized to generate new tokens, which can be allocated to specific addresses, such as user wallets or the contract owner's wallet. This feature is commonly employed in various decentralized finance (DeFi) and non-fungible token (NFT) projects to facilitate token issuance and distribution. The Presence of Minting Function module is designed to quickly identify the presence and implementation of minting functions in a smart contract. Mint functions play a crucial role in creating new tokens and transferring them to the designated user's or owner's wallet. This process significantly contributes to increasing the overall circulation of the tokens within the ecosystem.

The tokens cannot be burned in this contract.

The token contract incorporates a burn function that enables the intentional reduction of token amounts, consequently diminishing the total supply. The execution of this burn function contributes to the creation of scarcity within the token ecosystem, as the overall availability of the token decreases.

The contract can be compiled with a more recent Solidity version

The contract should be written using the latest Solidity pragma version as it comes with numerous bug fixes. Utilizing an outdated version exposes the contract to vulnerabilities associated with known issues that have been addressed in subsequent updates. Therefore, it is essential to stay current with the latest Solidity version to ensure the robustness and security of the contract against potential vulnerabilities.

This is not a proxy-based upgradable contract.

The Proxy-Based Upgradable Contract module is dedicated to identifying the presence of upgradeable contracts or proxy patterns within a smart contract. The utilization of upgradeable contracts or proxy patterns enables contract owners to make dynamic changes to various aspects, including functions, token circulation, and distribution, without requiring a complete redeployment of the contract.

Owners cannot blacklist tokens or users.

This module is designed to identify whether the owner of a smart contract has the capability to blacklist specific tokens or users. In a scenario where owners possess the authority to blacklist, all transactions related to the blacklisted entities will be immediately halted. Ownership privileges that include the ability to blacklist tokens or users can be a critical feature in certain use cases, providing the owner with control over potential malicious activities, compliance issues, or other concerns. However, in situations where this authority is abused or misapplied, it can lead to unintended consequences and user dissatisfaction.

Is ERC-20 token.

A token is expected to adhere to the established standards of the ERC-20 token specification, encompassing the inclusion of all necessary functions with standardized names and arguments as defined by the ERC-20 standard.

This is a Pausable contract.

Pausable contracts refer to contracts that can be intentionally halted by their owners, temporarily preventing token holders from engaging in buying or selling activities. This pause mechanism allows contract owners to exert control over the token's functionality, introducing a temporary suspension in trading activities for various reasons such as security concerns, updates, or regulatory compliance adjustments.

Critical functions that add, update, or delete owner/admin addresses are detected.

A smart contract within the Web3 ecosystem that incorporates critical administrative functions can potentially compromise the transparency and intended objectives of the contract. It is imperative to conduct a thorough examination of these functions, especially in the realm of Web3 smart contracts. Minimizing administrative functions in a token contract within the Web3 framework can significantly reduce the likelihood of complications and enhance overall efficiency and clarity.

The contract cannot be self-destructed by owners.

The SELFDESTRUCT opcode is a critical operation in Ethereum smart contracts, allowing a contract to autonomously terminate itself. When invoked, this opcode deallocates the contract, freeing up storage and computational resources on the Ethereum blockchain. Notably, the remaining Ether in the contract is sent to a specified address, ensuring a responsible handling of funds.

The contract is not vulnerable to ERC-20 approve Race condition vulnerability.

The ERC-20 race condition arises when two or more transactions attempt to interact with the same ERC-20 token contract concurrently. This scenario can result in conflicts and unexpected behavior due to the non-atomic nature of certain operations in the contract. Atomicity refers to the concept that an operation is indivisible and occurs as a single, uninterruptible unit.

The contracts are not using functions that can only be called by the owners.

An overpowered owner risk occurs when a contract has numerous functions that only the owner can execute. This can lead to centralization issues and potential abuse, as the owner has disproportionate control over the contract's operations.

The contract does not have a cooldown feature.

Cooldown functions, a crucial aspect in the smart contract landscape, are employed to temporarily suspend trading activities or other contract workflows. The mechanism introduces a time-based delay, effectively preventing users from repeatedly executing transactions or engaging in rapid buying and selling of tokens. Cooldown functions are used to halt trading or other contract workflows for a certain amount of time so as to prevent users from repeatedly executing transactions or buying and selling tokens.

Owners can whitelist tokens or users.

This empowers the contract owner to selectively grant privileges to users, such as exemption from fees or access to unique contract features.

Owners cannot set or update Fees in the contract.

In the context of smart contracts, fees are essential components that may be associated with various functionalities, such as transactions, token transfers, or other specific actions. The ability for owners to set or update fees is particularly valuable in scenarios where fee adjustments are needed to align with market conditions, regulatory requirements, or project-specific considerations. The Owners Can Set or Update Fees module focuses on identifying the capability within a smart contract for owners to establish or modify fees. This feature allows contract owners to have control over the fee structure within the contract, providing flexibility and adaptability to changing circumstances.

Hardcoded addresses were not found.

The inclusion of a fixed or hardcoded address within a smart contract has the potential to pose significant challenges in the future, particularly concerning the contract's adaptability and upgradability. This static reference to an address may impede the seamless implementation of updates or modifications to the contract, hindering its ability to evolve in response to changing requirements. Such rigidity may result in complications and obstacles when attempting to enhance or alter the smart contract's functionality over time.

The contract does not have any owner-controlled functions modifying token balances.

The Owners Updating Token Balance module is focused on identifying situations where a smart contract has functions controlled by owners that allow them to update token balances for other users or the contract. If a contract permits owners to manipulate token balances, it can have significant implications on user holdings and overall contract integrity. In some scenarios, contracts may provide owners with functions that enable the manual adjustment of token balances. While this feature can be legitimate for specific use cases, such as token distribution or rewards, it also introduces potential risks. Allowing owners to arbitrarily update token balances may lead to vulnerabilities, manipulation, or unintended changes in the token ecosystem.

No such functions retrieving ownership were found.

The Function Retrieving Ownership module serves the purpose of swiftly and efficiently retrieving ownership-related information within a smart contract. This functionality is vital for projects seeking to access and manage ownership data seamlessly. Utilizing this module, developers can streamline the process of obtaining ownership details, contributing to the effective administration of ownership-related functions within the ecosystem.

Absence of Malicious Typecasting.

Malicious typecasting, particularly the conversion of uint160 values to addresses, is a tactic often used by scammers to create deceptive addresses that can bypass standard detection mechanisms, facilitating fraudulent activities.

No such functions having totalSupply function update were found.

A fixed supply token is critical when the token's value is tied to scarcity or when precise control over inflation or deflation is required. Without a fixed supply, the contract could introduce unexpected inflation, devalue the token, or erode trust in the token's consistency.

No such functions having gas abuse via malicious minting.

Gas abuse refers to patterns within smart contracts that manipulate gas consumption in ways that unnecessarily increase transaction costs for users. This can occur through various mechanisms designed to exploit gas inefficiencies or inflate gas usage, shifting the financial burden onto users without their knowledge.

No hidden owner detected

The Hidden Owner check identifies whether there are any hidden owner roles within the contract. Hidden ownership can allow unauthorized access and control over contract functions, which poses a risk to users and stakeholders.

No such functions having addresses with special access.

Special permissions granted to non-owner addresses allow them to execute specific functions with elevated access. This can introduce security risks, as these privileged addresses may perform critical operations that impact the contract's state or user funds. If not properly managed or monitored, these permissions could lead to unauthorized or malicious actions, compromising the contract's integrity.

Absence of external call risk in critical functions.

This check identifies risks associated with external calls within critical functions. External calls can introduce vulnerabilities such as unexpected state changes, or dependencies on external contracts, which may compromise the integrity and reliability of the function’s execution.

Issue Type

PRESENCE OF MINTING FUNCTION

Action Taken

⚠ *Pending Fix*

Description

Minting functions are often utilized to generate new tokens, which can be allocated to specific addresses, such as user wallets or the contract owner's wallet. This feature is commonly employed in various decentralized finance (DeFi) and non-fungible token (NFT) projects to facilitate token issuance and distribution. The Presence of Minting Function module is designed to quickly identify the presence and implementation of minting functions in a smart contract. Mint functions play a crucial role in creating new tokens and transferring them to the designated user's or owner's wallet. This process significantly contributes to increasing the overall circulation of the tokens within the ecosystem.

Remediation

It is important to ensure the minting function includes proper access control mechanisms to restrict token minting to authorized addresses only, thereby preventing unauthorized or excessive token creation.

File Location	Line No.
GameToken.sol	L67 - L112

Issue Type

SOLIDITY PRAGMA VERSION

Action Taken

⚠ *Pending Fix*

Description

The contract should be written using the latest Solidity pragma version as it comes with numerous bug fixes. Utilizing an outdated version exposes the contract to vulnerabilities associated with known issues that have been addressed in subsequent updates. Therefore, it is essential to stay current with the latest Solidity version to ensure the robustness and security of the contract against potential vulnerabilities.

Remediation

Update the Solidity pragma version to the latest stable version to benefit from the latest bug fixes and security enhancements.

File Location	Line No.
GameToken.sol	L2 - L2

Issue Type

PAUSABLE CONTRACTS

Action Taken

⚠ *Pending Fix*

Description

Pausable contracts refer to contracts that can be intentionally halted by their owners, temporarily preventing token holders from engaging in buying or selling activities. This pause mechanism allows contract owners to exert control over the token's functionality, introducing a temporary suspension in trading activities for various reasons such as security concerns, updates, or regulatory compliance adjustments.

Remediation

Implement the pause() and unpause() functions in your contract and secure them with the onlyOwner modifier. This ensures that only the contract owner has the authority to change the paused state of the contract. Additionally, verify that the owner is correctly set and that the access control mechanisms are thoroughly tested to prevent any unauthorized actions.

File Location	Line No.
GameToken.sol	L166 - L168
GameToken.sol	L170 - L172

Issue Type

CRITICAL ADMINISTRATIVE FUNCTIONS

Action Taken

⚠ *Pending Fix*

Description

A smart contract within the Web3 ecosystem that incorporates critical administrative functions can potentially compromise the transparency and intended objectives of the contract. It is imperative to conduct a thorough examination of these functions, especially in the realm of Web3 smart contracts. Minimizing administrative functions in a token contract within the Web3 framework can significantly reduce the likelihood of complications and enhance overall efficiency and clarity.

Remediation

Review and minimize critical administrative functions within the smart contract to only include essential functionalities necessary for contract management and operation.

File Location	Line No.
GameToken.sol	L7 - L7

Issue Type

OWNERS WHITELISTING TOKENS/USERS

Action Taken

⚠ *Pending Fix*

Description

This empowers the contract owner to selectively grant privileges to users, such as exemption from fees or access to unique contract features.

Remediation


Ensure that the contract owner's ability to whitelist tokens or users is limited to necessary and legitimate use cases, such as granting special privileges or access to specific features, and implement strict access controls to prevent unauthorized whitelisting actions.

File Location	Line No.
GameToken.sol	L12 - L12

04. Findings Summary

BROT Token
File Scan

Security Score	Scan duration	Lines of code
60.82/100	4 secs	154



1	0	1	5	50	25
Crit	High	Med	Low	Info	Gas

This audit report has not been verified by the SolidityScan team. To learn more about our published reports. click here